



Kepu Water

# Fountain Components

Stainless Steel&Brass Fountain Nozzles, Submersible Fountain Lights, Underwater Junction Boxes, Fountain Accessories

## UNDERWATER FOUNTAIN LIGHTS

### KP-UL-005



Shell material	Diagram		
304 Stainless Steel		D1=150mm D2=135mm D3=25mm H=80mm IP rating:IP68	

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
150	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
150	9	9W	12V、24V	R/Y/G/B/W/WW/RGB

### KP-UL-006



Shell material	Diagram		
Cast 304 SS		D1=80mm D2=57mm H=75mm IP rating:IP68	

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
80	3	3W	12V、24V	R/Y/G/B/W/WW/RGB

### KP-UL-007



Shell material	Diagram		
Cast 304 SS		D1=128mm D2=103mm H=107mm IP rating:IP68	

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
128	5	5W	12V、24V	R/Y/G/B/W/WW/RGB
128	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
128	9	9W	12V、24V	R/Y/G/B/W/WW/RGB

**KP-UL-008**



Shell material	Diagram		
Cast 304 SS			D1=195mm D2=160mm H=140mm IP rating:IP68

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
195	12	12W	12V、24V	R/Y/G/B/W/WW/RGB
195	15	15W	12V、24V	R/Y/G/B/W/WW/RGB

**KP-UL-009**



Shell material	Diagram		
304 Stainless Steel			D1=160mm D2=135mm H=141mm IP rating:IP68

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
160	15	15W	24V	R/Y/G/B/W/WW/RGB
160	18	18W	24V	R/Y/G/B/W/WW/RGB

**KP-UL-010**



Shell material	Diagram		
304 Stainless Steel			D1=125mm D2=78mm H=183.5mm IP rating:IP68

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
125	3	3W	12V、24V	R/Y/G/B/W/WW/RGB
125	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
125	9	9W	12V、24V	R/Y/G/B/W/WW/RGB

**KP-UL-011**



Shell material	Diagram
304 Stainless Steel	<p>D1=105mm H=200mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
105	3	3W	12V、24V	R/Y/G/B/W/WW/RGB
105	9	9W	12V、24V	R/Y/G/B/W/WW/RGB

**KP-UL-012**



Shell material	Diagram
304 Stainless Steel	<p>D1=230mm D2=120mm D3=42/50 mm H=80mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
230	6/9/12	6W/9W/12W	12V、24V	R/Y/G/B/W/WW/RGB
230	6/9	18W/27W	24V	R/Y/G/B/W/WW/RGB

**KP-UL-013**

**Matching to our 1" brass&SS splash pad nozzles-Flush Mount**



Shell material	Diagram
304 Stainless Steel	<p>D1=300mm D2=170mm D3=42/50/65/80 mm H=90mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
300	9	9W	12V、24V	R/Y/G/B/W/WW/RGB
300	12	12W	12V、24V	R/Y/G/B/W/WW/RGB
300	15/18	15W/18W	12V、24V	R/Y/G/B/W/WW/RGB
300	9	27W	12V、24V	R/Y/G/B/W/WW/RGB
300	12/18	36W/54W	12V、24V	R/Y/G/B/W/WW/RGB

**KP-UL-014**

**Matching to our 1" brass&SS splash pad nozzles-Flush Mount**




Shell material	Diagram
304 Stainless Steel	<p>D1=270mm D2=140mm D3=42/50/65 mm H=85mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
270	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
270	9	9W	12V、24V	R/Y/G/B/W/WW/RGB
270	12	12W	12V、24V	R/Y/G/B/W/WW/RGB
270	6	18W	12V、24V	R/Y/G/B/W/WW/RGB
270	9/12	27W/36W	12V、24V	R/Y/G/B/W/WW/RGB

**KP-UL-015**

**Matching to our 1" brass&SS splash pad nozzles-Flush Mount**



Shell material	Diagram
304 Stainless Steel	<p>D1=260mm D2=170mm D3=65/80 mm D4=230mm H=85mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
260	15	15W	24V	R/Y/G/B/W/WW/RGB
260	24	24W	24V	R/Y/G/B/W/WW/RGB
260	9	27W	24V	R/Y/G/B/W/WW/RGB
260	12	36W	24V	R/Y/G/B/W/WW/RGB
260	18	54W	24V	R/Y/G/B/W/WW/RGB

**KP-UL-016**

**Matching to our 1" brass&SS splash pad nozzles-Flush Mount**



Shell material	Diagram
304 Stainless Steel	<p>D1=230mm D2=170mm D3=42/50/65/80 mm D4=215mm H=90mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
230	9/12	9W/12W	12V、24V	R/Y/G/B/W/WW/RGB
230	15/18	15W/18W	24V	R/Y/G/B/W/WW/RGB
230	9/12	27W/36W	24V	R/Y/G/B/W/WW/RGB

**KP-UL-017**



Shell material	Diagram			
304 Stainless Steel				
	D1=220mm	D2=110mm	D3=32/35 mm	D4=145mm
	H=70mm	IP rating:IP68		
Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
220	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
220	9	9W	12V、24V	R/Y/G/B/W/WW/RGB
220	6	18W	12V、24V	R/Y/G/B/W/WW/RGB

**KP-UL-018**

**Matching to our 1" brass&SS splash pad nozzles-Flush Mount**



Shell material	Diagram			
304 Stainless Steel				
	D1=220mm	D2=140mm	D3=42/50/65 mm	D4=190mm
	H=80mm	IP rating:IP68		
Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
220	9	9W	12V、24V	R/Y/G/B/W/WW/RGB
220	12	12W	24V	R/Y/G/B/W/WW/RGB
220	9	27W	24V	R/Y/G/B/W/WW/RGB
220	12	36W	24V	R/Y/G/B/W/WW/RGB

**KP-UL-019**

**Matching to our 1" brass&SS splash pad nozzles**



Shell material	Diagram			
304 Stainless Steel				
	D1=190mm	D2=120mm	D3=42/50/65 mm	D4=170mm
	H=75mm	IP rating:IP68		
Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
190	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
190	9	9W	24V	R/Y/G/B/W/WW/RGB
190	12	12W	24V	R/Y/G/B/W/WW/RGB
190	6	18W	24V	R/Y/G/B/W/WW/RGB
190	9	27W	24V	R/Y/G/B/W/WW/RGB

**KP-UL-020**



Shell material	Diagram
304 Stainless Steel	<p>D1=180mm D2=110mm D3=25/32 mm D4=145mm H=70mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
180	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
180	9	9W	12V、24V	R/Y/G/B/W/WW/RGB
180	6	18W	12V、24V	R/Y/G/B/W/WW/RGB

**KP-UL-021**



Shell material	Diagram
304 Stainless Steel	<p>D1=165mm D2=110mm D3=25/32 mm D4=145mm H=80mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
165	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
165	9	9W	12V、24V	R/Y/G/B/W/WW/RGB
165	6	18W	12V、24V	R/Y/G/B/W/WW/RGB

**KP-UL-022**



Shell material	Diagram
304 Stainless Steel	<p>D1=170mm D4=120mm D3=42/50 mm H=75mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
170	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
170	9	9W	12V、24V	R/Y/G/B/W/WW/RGB
170	12	12W	24V	R/Y/G/B/W/WW/RGB
170	6	18W	24V	R/Y/G/B/W/WW/RGB
170	9	27W	24V	R/Y/G/B/W/WW/RGB



**KP-UL-023**



Shell material	Diagram			
304 Stainless Steel				<p>D1=250mm D2=170mm D3=65/80 mm D4=230mm H=80mm IP rating:IP68</p>
Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
250	24	24W	24V	R/Y/G/B/W/WW/RGB
250	18	54W	24V	R/Y/G/B/W/WW/RGB

**KP-UL-024**

**1" center female thread, thread to male 1" nozzles**



Shell material	Diagram			
304 Stainless Steel				<p>D1=145mm D2=110mm D3=1" Female H=80mm IP rating:IP68</p>
Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
145	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
145	9	9W	12V、24V	R/Y/G/B/W/WW/RGB
145	6	18W	12V、24V	R/Y/G/B/W/WW/RGB
145	9	27W	24V	R/Y/G/B/W/WW/RGB

**KP-UL-025**

**Matching to our 1" brass&SS splash pad nozzles**



Shell material	Diagram			
304 Stainless Steel				<p>D1=215mm D4=170mm D3=42/50/65/80 mm H=86mm IP rating:IP68</p>
Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
215	12	12W	24V	R/Y/G/B/W/WW/RGB
215	15	15W	24V	R/Y/G/B/W/WW/RGB
215	18	18W	24V	R/Y/G/B/W/WW/RGB
215	24	24W	24V	R/Y/G/B/W/WW/RGB
215	9	27W	24V	R/Y/G/B/W/WW/RGB
215	12	36W	24V	R/Y/G/B/W/WW/RGB
215	18	54W	24V	R/Y/G/B/W/WW/RGB

**KP-UL-026**

**Matching to our 1" brass&SS splash pad nozzles**



Shell material	Diagram
304 Stainless Steel	<p>D1=190mm D4=140mm D3=42/50/65 mm H=85mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
190	9	9W	24V	R/Y/G/B/W/WW/RGB
190	12	12W	24V	R/Y/G/B/W/WW/RGB
190	6	18W	24V	R/Y/G/B/W/WW/RGB
190	9	27W	24V	R/Y/G/B/W/WW/RGB

**KP-UL-027**



Shell material	Diagram
304 SS plate&aluminum body Center hole: 38mm	

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
210/180	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
210/180	9	9W	12V、24V	R/Y/G/B/W/WW/RGB
210/180	12	12W	24V	R/Y/G/B/W/WW/RGB

**KP-UL-028**



Shell material	Diagram
304 SS plate&aluminum body Center hole: 38/48 mm	

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
200/180	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
200/180	9	9W	12V、24V	R/Y/G/B/W/WW/RGB
200/180	12	12W	24V	R/Y/G/B/W/WW/RGB
200	15	15W	24V	R/Y/G/B/W/WW/RGB



### KP-UL-029



Shell material	Diagram			
304 SS plate&aluminum body				Center hole=38mm IP rating:IP68
Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
160	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
160	9	9W	12V、24V	R/Y/G/B/W/WW/RGB

### KP-UL-030



Shell material	Diagram			
304 Stainless Steel				D1=300/250/215 D2=230/188/169 H=185/150/148 IP rating:IP68
Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
300	72	72W	24V	R/Y/G/B/W/WW/RGB
300	60	180W	24V	R/Y/G/B/W/WW/RGB
250	36	36W	24V	R/Y/G/B/W/WW/RGB
250	45	45W	24V	R/Y/G/B/W/WW/RGB
250	24	72W	24V	R/Y/G/B/W/WW/RGB
250	36	108W	24V	R/Y/G/B/W/WW/RGB
215	24	24W	24V	R/Y/G/B/W/WW/RGB
215	30	30W	24V	R/Y/G/B/W/WW/RGB
215	18	54W	24V	R/Y/G/B/W/WW/RGB
215	24	72W	24V	R/Y/G/B/W/WW/RGB

### KP-UL-031



Shell material	Diagram			
304 Stainless Steel				D1=250mm D2=188mm H=148mm IP rating:IP68
Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
250	36	36W	24V	R/Y/G/B/W/WW/RGB
250	45	45W	24V	R/Y/G/B/W/WW/RGB
250	18	54W	24V	R/Y/G/B/W/WW/RGB
250	24/36	72W/108W	24V	R/Y/G/B/W/WW/RGB

### KP-UL-032



Shell material	Diagram
304 Stainless Steel	<p>D1=215mm D2=169mm H=148mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
215	24	24W	24V	R/Y/G/B/W/WW/RGB
215	30	30W	24V	R/Y/G/B/W/WW/RGB
215	12	36W	24V	R/Y/G/B/W/WW/RGB
215	18	54W	24V	R/Y/G/B/W/WW/RGB
215	24	72W	24V	R/Y/G/B/W/WW/RGB
215	30	90W	24V	R/Y/G/B/W/WW/RGB

### KP-UL-033



Shell material	Diagram
304 Stainless Steel	<p>D1=190mm D2=144mm H=105mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
190	18	18W	24V	R/Y/G/B/W/WW/RGB
190	24	24W	24V	R/Y/G/B/W/WW/RGB
190	6/9	18W/27W	24V	R/Y/G/B/W/WW/RGB
190	12/18	36W/54W	24V	R/Y/G/B/W/WW/RGB

### KP-UL-034



Shell material	Diagram
304 Stainless Steel	<p>D1=170mm D2=123mm H=93mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
170	12	12W	24V	R/Y/G/B/W/WW/RGB
170	15	15W	24V	R/Y/G/B/W/WW/RGB
170	18	18W	24V	R/Y/G/B/W/WW/RGB
170	6	18W	24V	R/Y/G/B/W/WW/RGB
170	9/12	27W/36W	24V	R/Y/G/B/W/WW/RGB

**KP-UL-035**



Shell material	Diagram
304 Stainless Steel	<p>D1=120mm D2=85mm H=120mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
120	3	3W	12V、24V	R/Y/G/B/W/WW/RGB
120	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
120	3	9W	12V、24V	R/Y/G/B/W/WW/RGB

**KP-UL-036**



Shell material	Diagram
304 Stainless Steel	<p>D1=145mm D2=105mm H=150mm IP rating:IP68</p>

Diameter(mm)	LEDs(pcs)	Power(w)	Voltage(v)	Color option
145	6	6W	12V、24V	R/Y/G/B/W/WW/RGB
145	9	9W	12V、24V	R/Y/G/B/W/WW/RGB
145	12	12W	24V	R/Y/G/B/W/WW/RGB
145	4	12W	24V	R/Y/G/B/W/WW/RGB
145	6	18W	24V	R/Y/G/B/W/WW/RGB
145	9	27W	24V	R/Y/G/B/W/WW/RGB